

TERRA SPIKE® SL

Deep spikerTo remove compactions on golf greens, tees, and sand-based sport fields





TERRA SPIKE® SL

The lightweight among the TERRA SPIKEs

With the TERRA SPIKE® SL. Wiedenmann has developed a machine which satisfies customer demands for low weight, high working depth and speed, at low drive and lifting power. Due to its low weight of less than 500 kg, operation with tractors in the 25 HP class is possible without any problems.

Time is money – this guiding principle applies today more than ever in professional turf maintenance. No matter whether you maintain sports fields or golf courses, the time for maintenance is continuously getting scarcer while the players' expectations on the quality of the turf are increasing at the same time. Regular deep spiking and deep aeration are one of the most important prerequisites for healthy root growth.

When compactions are broken open, the grass roots can penetrate deeper into the ground and make better use of water and nutrients. The water flow and air halance are improved, thatch is removed and the shear strength is increased. However in the past, despite all technical innovations. this maintenance work was always very time-consuming. Wiedenmann has revolutionised turf maintenance and sets new standards with respect to speed, productivity and labour quality. You can save up to 60 % of your previous time for performing these maintenance measures. Just as important for us as productivity is your health. We have, therefore, fitted the inimitable damping system VibraStop into the TERRA SPIKE® SL so that the work is not only carried out rapidly, but also free of stress for you and your tractor.

The TwinDrive drive concept can be furnished with various transmission ratios, so that the crankshaft speed can be optimally adapted to the performance of the available tractor.

Do not waste your valuable time on the correct setting of the working depth or the loosening angle. With the exclusive QuickSet system, you can perform these settings without tools in just a few manual operations.

The central adjustment of the loosening angle allows you to set the optimal adaptation of the loosening intensity to the respective ground conditions and degree of compaction. With the exclusive QuickChange system, arduous and time-consuming tine replacements are a chore of the past.

The TERRA SPIKE® SL is extremely service-friendly. The machine does no longer have any metallic return springs, and the number of lubricating points has been reduced to a minimum.

The high productivity of the TERRA SPIKE® SL will also convince you.



When using coring tines on the TERRA SPIKE® SL, the cores can automatically be aligned in the swath by means of the optional swath board. This considerably facilitates the subsequent take-up of the cores.



VibraStop

The exclusive VibraStop system protects the driver from vibrations and the tractor and tools from damages caused by shocks and vibrations. The resulting smooth running is unique. VibraStop meets all requirements of the EU Directive 78/764/EEC with respect to whole- body vibrations. Vibrations that act on the operator are significantly reduced by the VibraStop system.

TwinDrive

The exclusive TwinDrive symmetrically introduces the power from two sides into the robust, continuous crankshaft. If harmful load peaks occur while working, e.g. if the tine strikes a stone, the impact is absorbed by the special v-ribbed belt on either side. The encapsulated drive is securely protected from dust and dirt.

The working depth is rapidly and correctly adjusted with a crank, without tools. The loosening angle is centrally adjustable with the supplied tool. The working depth and the loosening angle are easily readable on a large scale.

QuickChange

The TERRA SPIKE® SL is equipped with exchangeable tine holders. The tine heads can be rapidly exchanged with only one screw. The machine is serially equipped with tine heads for tines with 12 mm intake. Tine heads for upwards ejecting coring tines are available as an option.

The stable, computer-optimised crankshaft is supported in large maintenance-free ball bearings. The smooth running of the TERRA SPIKE® SL will also surprise you. The gear box has been moved forward in order to optimise the position of the centre of gravity.

The optional turf retainer prevents damage to turf that is poorly rooted. The turf retainer has been designed to match tine spacing.

Hole spacing of 55 mm at a speed of 1.6 km/h

2.200 m²/h

Max. area coverage for crankshaft speed 485 RPM

Descriptions and illustrations are not binding. Changes in design and execution reserved.

TECHNICAL DATA Working width in mm: 1,400 Weight with rear roller in kg approx.: 470 Maximum working depth in mm: Dimensions L/W/H in mm approx.: 980/1,770/1,120 210 QuickSet/QuickChange/VibraStop/TwinDrive Maximum permissible PTO output in kW/HP: 26 kW/35 HP Series Minimum lifting capacity of the tractor in kg: 625 Solid tines diameter in mm: 8, 10, 12, 16 Coring tines diameter in mm: 10, 12, 16, 20 Rear roller Series Swath board Optional Turf retainer Optional Exchangeable tine heads for upwards ejecting coring tines Optional Max. area coverage for crankshaft speed 280 RPM Hole spacing from 55 mm at a speed of 0.9 km/h 1 250 m²/h Max. area coverage for crankshaft speed 360 RPM Hole spacing of 55 mm at a speed of 1.2 km/h 1.660 m²/h

Tine programme

The TERRA SPIKE® SL can be equipped with solid tines from 8-16 mm diameter, as well as with coring tines from 10-20 mm diameter. All these tines fit into the standard tine heads with 12 mm intake. Alternatively, Wiedenmann offers tine heads for upwards ejecting coring tines with 12 and 16 mm diameter









Solutions as different as the seasons.

Whether spring, summer, autumn or winter – whether professional turf and golf course maintenance, dirt cleaning, or winter service: you can rely on machines from Wiedenmann GmbH in every season.

As one of the world-wide leading manufacturers of high-quality accessory equipment for compact tractors and light municipal vehicles, we offer demand-driven solutions for turf regeneration, take-up and removal of grass and foliage, mowing and turf sweeping, as well as snow and dirt sweepers, snow-rake blades and winter gritting equipment.

Our workforce of 210 has regularly set new standards with regard to innovative technological solutions and uncompromising quality.

Further information:	

Wiedenmann GmbH Am Bahnhof | 89192 Rammingen | GERMANY Telefon +49 7345 953-0 | Telefax +49 7345 953-233 info@wiedenmann.com

